

Selection Guide



Model Name	UNO-1252G	UNO-1372G	UNO-1483G	UNO-3283G	UNO-3382G/3384G	UNO-3483G
CPU	Intel® Quark 400 MHz	Intel® Atom™ E3845 1.91GHz	Intel® 4th Gen. Core™ i3-4010U 1.7GHz	Intel® Core™ i CPU	Intel® Core™ i7-4650U 1.7Hz	Intel® Core™ i7-3612QE
Onboard RAM	256MB DDR3 SDRAM	4GB DDR3L SDRAM	8GB DDR3L SDRAM	8GB DDR3L SDRAM	8GB DDR3L SDRAM	8GB SO-DIMM DDR3/DDR3L
Battery-Backup SDRAM	-	-	-	-	On board MRAM 512K	-
Display	-	HDMI, VGA	DP, VGA	DVI, HDMI	DVI, DP (disabled when attached to display module)	VGA, HDMI
Audio	-	Line-out	Line-out	Mic in, Line out (pin header)	N/A (built-in Line-in/out/Mic, I/O through iDoor)	Mic in, Line out (pin header)
Serial Ports	1 x RS-232, 1 x RS-485	1 x RS-232, 1 x RS-422/485	1 x RS-232, 2 x RS-422/485	2 x RS-232/422/485 with DB9 connection	RS-232/422/485 x 1 (isolation)	1 x RS-232, 1 x RS-232/422/485 with DB9 connection (pin header)
Ethernet Ports	2 x 10/100 Base-T	3 x 10/100/1000 Base-T	4 x 10/100/1000 Base-T	2 x 10/100/1000 Base-T RJ-45 (support IEEE1588)	2 x 10/100/1000 Base-T RJ-45 (support IEEE1588)	2 x 10/100/1000 Base-T RJ-45 (support IEEE1588)
USB Ports	1 x USB 2.0 1 x USB 2.0 client	2 x USB 2.0 1 x USB 3.0	2 x USB 2.0 2 x USB 3.0	2 x USB 2.0 4 x USB 3.0	2 x USB 2.0 2 x USB 3.0	2 x USB 2.0 2 x USB 3.0
PCIe/PCI Expansion	2 x Mini PCIe	2 x Mini PCIe	1 x PCIe x 1 2 x Mini PCIe	1 x PCIe x 16, 2 x PCI	UNO-3382G: 2 x Mini PCIe UNO-3384G: 2 x Mini PCIe, 2 x PCI/PCIe (2 x PCI, 1 x PCIe x1+1 x PCIe x 4, 1 x PCI + 1 x PCIe x 4)	1 x PCIe x 4, 3 x Mini PCIe (2 x full, 1 x half)
Digital I/O	4-ch DI, 4-ch DO	4-ch DI, 4-ch DO	4-ch DI, 4-ch DO	-	-	-
CFast Slots	-	-	-	CFast x 1	CFast x 1	-
2.5" HDD Expansion	-	1 x SATA 6Gb/s	1 x SATA 6Gb/s	Two built-in 2.5" SATA HDD brackets with support for RAID 0/1	Two built-in 2.5" SATA HDD brackets with support for RAID 0/1	Two built-in 2.5" SATA HDD brackets with support for RAID 0/1
Operating Systems	Linux	Windows 7/8, WES7/WES8, Linux	Windows 7/8, WES7/WES8, Linux	WinXP, Win7/8, WES7/8, Win8, WES, Linux	Linux, Win 7, WES 7, Win 8, Win	WinXP, Win7/8, WES7/8, Win8, WES, Linux
Mounting	DIN-rail Mount	DIN-rail/Wall Mount	DIN-rail/Wall Mount	Wall, Stand, Panel Mount	Book Mount	Enclosure Mount
Power Input Range	12/24Vdc ± 15%	12/24Vdc ± 20%	12/24Vdc ± 20%	12/24Vdc ± 20%	24Vdc ± 20%	12/24Vdc ± 20%
Operating Temperature	-20 ~ 60°C (-4 ~ 140°F)	-20 ~ 60°C (-4 ~ 140°F)	-20 ~ 60°C (-4 ~ 140°F)	-20 ~ 60°C (-4 ~ 140°F)	-20 ~ 60°C (-4 ~ 140°F)	-20 ~ 60°C (-4 ~ 140°F)
Power Consumption Typical	6W	24W	41W	50W	45W	50W
Power Requirement	12W, 24Vdc @ 0.5A	36W, 24Vdc @ 1.5A	60W, 24Vdc @ 2.5A	12V/24Vdc @ 5A	24Vdc @ 4.5A	12V/24Vdc @ 4A
Dimensions (W x D x H)	70 x 90 x 100 mm (2.76" x 3.54" x 3.94")	85 x 139 x 152 mm (3.3" x 5.5" x 6.0")	106 x 139 x 198 mm (4.2" x 5.8" x 7.8")	305 x 238 x 225 mm (120.1" x 93.7" x 88.58")	UNO-3382G: 254 x 207 x 65.2 mm (100" x 81.5" x 25.7") UNO-3384G: 254 x 207 x 103.2 mm (100" x 81.5" x 40.6")	305 x 82 x 225 mm (120.1" x 32.3" x 88.6")

Advantech iDoor Module

Memory/Storage/External I/O Communication FieldBus Digital / Analog I/O

PCM-2300MR MR4A16B, MRAM, 2MByte	PCM-2300TP TPM Compliant with TCG 1.2	PCM-23C1CF CFast, Ejection Type 1, CFast x 1	PCM-23U1DG Locked USB Slot for USB Dongle, USB x 1
PCM-24D2R2/24D2R4 OXPcie-952 UART, Isolated RS-232, 422/485, DB9 x 2	PCM-24D4R2/24D4R4 OXPcie-954 UART, Non-Isolated RS-232, 422/485, DB37 x 1	PCM-24R2PE Intel i350, GbE, PoE IEEE 802.3af, PD, RJ45 x 2	PCM-24R2GL Intel i350 PCIe, GbE, LAN Mini Card, RJ45 x 2
PCM-24R1TP Intel 82574L, GbE, IEEE 1588 PTP, RJ45 x 1	PCM-24U2U3 USB 3.0 Mini Card, USB x 2	PCM-24S2WF 802.11 a/b/g/n 2T2R w/ BT4.0, Atheros AR9462, SMA x 2	PCM-24S23G 6-band HSPA Cellular Module, SIM Holder+GPS, SMA x 2
PCM-24S24G LTE Bands, UMTS/HSPA Bands, GPS/GPRS Bands, SMA x 2	PCM-26D2CA SJA1000 CANBus, CANOpen, DB9 x 2	PCM-26D1PB Hilscher netX100 FieldBus, ProfiBus, DB9 x 1	PCM-27D24DI Digital I/O, 16 DI / 8 DO, Isolation, DB37 x 1

Advantech Innovative Design Concept- Simple, Flexible, Reliable

As a leading provider of Industrial PC, Advantech devoted to innovation product/service development. To be the pioneer in intelligent automation technology, the i-concept represents the intelligent, integrated and intuitive design which covers the innovation of service model, user behavior and cutting-edge technology that opens a new era of industrial automation.



An integrated intelligent key brings simplified intuitive operation for configuring your automation panel. With a flexible software design, customized functions are easier to carry out.



A standardized modular Interface which offers flexible expansion to increase the number of applications and expand system functions through the variety of standardized modular I/Os.



A Reliable Long Distance Transmission Technology which transfers video signals and touch control over a single Ethernet cable which overcomes interference in harsh environments not only for data connections, but also for a cost effective multiple display solution.

Regional Service & Customization Centers

China Kunshan 86-512-5777-5666	Taiwan Taipei 886-2-2792-7818	Netherlands Eindhoven 31-40-267-7000	Poland Warsaw 48-22-33-23-740 / 41	USA/ Canada Milpitas, CA 1-408-519-3898
---	--	---	---	--

Worldwide Offices

Greater China

China	Toll Free	800-810-0345
	Beijing	86-10-6298-4346
	Shanghai	86-21-3632-1616
	Shenzhen	86-755-8212-4222
	Chengdu	86-28-8545-0198
	Hong Kong	852-2720-5118

Taiwan

Toll Free	0800-777-111
Neihu	886-2-2792-7818
Xindian	886-2-2218-4567
Taichung	886-4-2378-6250
Kaohsiung	886-7-229-3600

Asia Pacific

Japan	Toll Free	0800-500-1055
	Tokyo	81-3-6802-1021
	Osaka	81-6-6267-1887
Korea	Toll Free	080-363-9494
	Seoul	82-2-3663-9494
Singapore	Singapore	65-6442-1000
Malaysia	Toll Free	1800-88-1809
	Kuala Lumpur	60-3-7725-4188
	Penang	60-4-537-9188
Indonesia	Jakarta	62-21-769-0525
Thailand	Bangkok	66-2-248-3140
India	Toll Free	1-800-425-5070
	Pune	91-20-39482075
	Bangalore	91-80-2545-0206
Australia	Toll Free	1300-308-531
	Melbourne	61-3-9797-0100
	Sydney	61-2-9476-9300

Europe

Toll Free	00800-2426-8080	
Germany	Munich	49-89-12599-0
	Hilden / D' dorf	49-2103-97-885-0
France	Paris	33-1-4119-4666
Italy	Milano	39-02-9544-961
Benelux & Nordics	Breda	31-76-5233-100
UK	Reading	44-0118-929-4540
Poland	Warsaw	48-22-33-23-740 / 41
Russia	Toll Free	8-800-550-01-50
	Moscow	7-495-232-1692

Americas

North America	Toll Free	1-888-576-9668
	Cincinnati	1-513-742-8895
	Milpitas	1-408-519-3898
	Irvine	1-949-420-2500
Brazil	Toll Free	0800-770-5355
	Saude-São Paulo	55-11-5592-5355
Mexico	Toll Free	1-800-467-2415
	Mexico City	52-55-6275-2777

More Information



860000145

ADVANTECH


Enabling an Intelligent Planet

<http://www.advantech.com>

Please verify specifications before quoting. This guide is intended for reference purposes only. All product specifications are subject to change without notice. No part of this publication may be reproduced in any form or by any means, electronic, photocopying, recording or otherwise, without prior written permission of the publisher. All brand and product names are trademarks or registered trademarks of their respective companies. © Advantech Co., Ltd. 2014

Advantech Control Cabinet PC

Designed for Machine Construction and Plant Engineering applications



- Introduction
- Product Features
- Intelligent Software
- Selection Guide



ADVANTECH

Enabling an Intelligent Planet


www.advantech.com

Advantech Control Cabinet PC

Wide Range of Product Form-factors for Different Mounting Scenarios of Cabinet Applications


Advantech's UNO-1000/3000 series of Embedded Control Cabinet PCs are fanless with high performance, multiple extensions, and ruggedized chassis with an embedded operating system (Windows CE, Windows XPE, Linux-Embedded). With iDoor Technology which supports automation feature extensions such as Fieldbus communication, Wi-Fi/3G, and Digital / Analog I/O. Versatile Mounting space DIN-Rail Mount, Wall Mount, Book Mount and Panel mount with easy installation indicated market segments. In terms of the type of mounting, with their Control Cabinet PC, they are suitable for IoT gateway, motion and vision applications. The design meets Class 1 Div. 2 & ATEX Certification for harsh environment applications.

Features & Benefits



Dual Power Input

Dual power input with wide range operating voltage is a fail-safe mechanism to reduce working unit maintaining down time by alternative power input source. And remote power on assists working units go back online from outside of the cabinet.




Multiple Expansion

UNO supports latest range of expansion interfaces including PCIe for high density I/O, iDoor for fieldbus modules, PCI for motion cards with easy installation captive thumb screws.




Enclosure Mount (UNO-3400)

Compact outside heatsink mounts through a corresponding cut-out in the cabinet or enclosure panel which integrated seals represent high performance as IP67.



Dual iDoor Expansion

Advantech's iDoor technology provides simple, flexible, and reliable expansion in high density systems using versatile color identification and multiple functions.



Built-in Digital I/O

Built-in DI/DO for simple I/O control, status detection, lighting control and event triggering in order to save extra cost and devices.



Dual Digital Display

Flexible display options provide resolutions of up to 4K/2K and provide excellent image quality.



C1D2/ATEX Certification

Meets and exists in hardly environment and applicable to operation in safety as Oil & Gas industry.

Easy Maintenance



Captive Thumb Screw

Operators can work efficiently with captive thumb screws as a superior tool to strengthen swapping HDD, CFast & PCI/PCland for maintaining storage and expansion devices.



Hot-swap RTC Battery

Removable RTC battery saves time and cost by avoiding disassembling the working unit and shutting down the whole operation.



Hot-swappable Storage

Hot-swap HDD/SSD let operators deploy software data or collect control data easily when maintaining working units without interruptions.

UNO-3200 Series



Remote Monitoring



Remote On/Off, KVM



System Configuration



Real-time Response



System Recovery



System Protection



UNO-1000 Series



UNO-3300 Series



UNO-3400 Series

Intelligent Software

WebAccess

Advantech WebAccess is a 100% web browser-based software package for HMI and SCADA with private cloud software architecture. All the features found in conventional HMI and SCADA software including Animated Graphics Displays, Real-time Data, Control, Trends, Alarms and Logs, are available in an standard web browser. WebAccess is built around the latest internet technologies.



SUSIAccess Remote Device Management

SUSIAccess Remote Device Management


SUSIAccess is an innovative remote management and cloud-based software preloaded in all Advantech embedded solutions, allowing the efficient and centralized remote monitoring and management of embedded devices in real-time, device health status, system configuration, system protection, and recovery & backup. SUSIAccess targets the needs of creating a more intelligent and interconnected embedded computing solution.

Panel Express

PanelExpress is a Windows based HMI runtime software, it enables you to utilize the resources of a PC such as computation power, multimedia and bigger screen to realize a high-end sophisticated HMI.




Versatile Mounting with Easy Installation




DIN-Rail Mount

UNO-1000 series can be painlessly installed on the rail with the sophisticated din-rail kit at the rear and R-angle design at the front.



Wall Mount

Easy pull-out operation is extremely convenient that advantage is suitable for all but the heavier installations.



Book Mount

The UNO-3300 offers an open and universal automation solution, saves space and allows quick installation in a control cabinet.



Panel Mount

The UNO-3400 series are designed for easier and quick installation in control cabinets. As UNO-3400 which has the Placing-and-Click snap connector which has further considered users' activity and then simplifies the installation procedures.